

# NLIS Tags



## Product Description

This round electronic tag guarantees security, usability and high retention, with a free rotating design that promotes rapid wound healing and maximises retention, as well as minimising abrasion of the animal's ear.

This tag is fully approved by NLIS and has been a stalwart in the Australian cattle industry since its release in 2008. Any attempt to separate the male tag from the female would damage both parts, making re-use impossible.

The tags are applied with the patented Z Tags No-Tear-Tagger™. The No-Tear-Tagger, thanks to its patent protected snap back jaw, virtually eliminates torn ears to drastically improve ear tag retention. The automatic opening of the applicator's jaws also improves health and safety as the tagger automatically releases the tag after application, allowing the user to maintain their grip on the tagger, while quickly getting their hand and arm away from cattle being tagged.

laboratory.



## Technical Specifications

Product Name	NLIS Tag
Dimension	F216: 31 mm Ø M210: 29 mm Ø
Weight	F216: 6.5 g M210: 1.7 g
Technology	HDX
Working Frequency	134.2 kHz
Certificate	ISO 11784/5 (942015)
Reading Distances	Up to 36 cm with the Tru-Test XRS2 EID Stick Reader Up to 100 cm with the Tru-Test XRP2 Panel Reader & Large Antenna
Applicator	Z Tags No-Tear-Tagger™

Although the information presented in this Product Information Sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Datamars. Performance data is typical only and variations due to component manufacturing tolerances are normal. Datamars reserves the right at any time to change performance characteristics or specifications without prior notice. © Datamars 2021 - All rights reserved.